

HG-GFS Gas cylinder cabinets

- to DIN EN 14470-2 (Indoor installation) and TRG 280 (Outdoor installation)



G90



G30



TRG280

Description:

The gas cylinder cabinets to DIN EN 14470-2 TRG 280 are fire chamber tested and type- tested and serve the safe and prescribed housing of 50l gas cylinders in buildings and outside areas.

The large inside height of the cylinder cabinets facilitates the easy mounting of gas supply stations. Standard contents consist of cylinder restraints, mounting rails for supply stations. Also permanently mounted at the bottom of the cabinet is a roll-in flap to facilitate the easy rolling in of cylinders in the G90 and G30 cabinets.

Mounted in the cabinet ceiling are diverse possibilities for the implementation of piping.

The gas cylinder cabinets are painted light grey RAL7035 as standard. On request, the cabinets can also be delivered in bright yellow RAL1004.

Gas cylinder cabinets G90 to DIN EN 14470-2 for indoor installation

Order No.	Cylinder	Doors	H x W x D / outer	H x W x D / inner	Weight
HG-GFS-901	1x50l	1	2050 x 600 x 615	1875 x 440 x 400	305kg
HG-GFS-902	3x50l	2	2050 x 900 x 615	1875 x 740 x 400	355kg
HG-GFS-903	3x50l+1x10l	2	2050 x 1200 x 615	1875 x 1040 x 400	485kg
HG-GFS-904	4x50l	2	2050 x 1400 x 615	1875 x 1240 x 400	525kg

Gas cylinder cabinets G30 to DIN EN 14470-2 for indoor installation

Order No.	Cylinder	Doors	H x W x D / outer	H x W x D / inner	Weight
HG-GFS-301	1x50l	1	2050 x 600 x 615	1900 x 490 x 450	290kg
HG-GFS-302	2x50l	2	2050 x 900 x 615	1900 x 790 x 450	340kg
HG-GFS-303	3x50l+1x10l	2	2050 x 1200 x 615	1900 x 1090 x 450	470kg
HG-GFS-304	4x50l	2	2050 x 1400 x 615	1900 x 1290 x 450	510kg

Gas cylinder cabinets to TRG 280 for outdoor installation

Order No.	Cylinder	Doors	H x W x D / outer	H x W x D / inner	Weight
HG-GFS-281	2 x50l	1	2150 x 740 x 470	2070 x 695 x 370	85kg
HG-GFS-282	3 x50l	2	2150 x 1040 x 470	2070 x 995 x 370	113kg
HG-GFS-283	4 x50l	2	2150 x 1390 x 470	2070 x 1345 x 370	138kg

Accessories:

Height adjustable lower shelf for max. 75kg weight over the complete cabinet width.

Side mounted height, adjustable cylinder holders for 10l cylinders.

Adjustable feet for easy alignment on uneven ground.

Hornung Quality standard

The company Hornung is certified to **DIN EN ISO 9001 and ISO 14001:2009.**

All single parts are manufactured, assembled and tested in house.

The finished parts are therefore under the criteria of our exact quality control with 100% final control.

Hornung GmbH
Rathenaustraße 55, 63263 Neu-Isenburg

Phone: +49 6102 7883-70
Fax: +49 6102 7883-40

www.hornung.org
info@hornung.org